

FP Stryder™ Anchorage Connector

- Easy, single hand installation.
- Easy to use, push button adjustment.
- Lightweight, only 4.5 lbs.
- Low friction wear pads with Teflon allows it to glide effortlessly along the beam flange.
- Integral load indicator alerts user if the unit has been exposed to a fall.
- Versatile design allows for mounting overhead or at worker's feet.
- Vernier adjustability allows for a secure fit and ¼" adjustment intervals
- Fits beam flange widths from 4" to 14"
- 400 lb working capacity
- Field serviceable
- Meets ANSI Z359.1, ANSI A10.32, and all applicable OSHA standards.



ManSafe Freestanding Force Post

- Does not attach to the working surface.
- Installer never has to lift more than 55 lbs (25kg).
- Used on nominally flat roofs up to a maximum pitch of 5°.
- Tested and approved for use on concrete, single ply membrane, asphalt-sanded, asphalt-stone chipped, and steel roof profiles.
- Post is omni-directional.



ITEM#	Description
FP-10055719	ManSafe freestanding post

ITEM#	Description
FP-10051455	FP Stryder anchorage connector, standard version



FP-FP6650



FP-FP5394



FP-FP86



FP-FP95M

Connectors

Provide safe and secure closure and are designed for easy operation even when wearing gloves. Rated for 5,000 lbs (22 kN).



ITEM#	Snap Hook
FP-FP6650	Double locking, drop forged steel snap hook 3/4" (19 mm) opening, 5-9/16" (141 mm) width

ITEM#	Large Locking Scaffold Hook
FP-FP5394	Drop forged scaffold hook; 2.5" gate opening

ITEM#	Carabiner
FP-FP86	Auto locking, drop forged, D-shaped carabiner 36/64" (14 mm) opening, 1-31/32" (60 mm) W, 4-3/32" (104 mm) L

ITEM#	Anchorage Connector Hardware
FP-FP95M	Aluminum shepherd's hook, 3.5" (89 mm) opening, 4" (102 mm) W, 13" (330 mm) L Use with: FP-FP08FT/16

ITEM#	First Man Up Accessory
FP-FP08FT/16	Fiberglass telescopic pole Length: 5m (16') Use with: FP-FP95M

Safe-T-Strap™

Low Rise - Consists of a 2" wide webbing, with a 2.5" D-ring attached at one end. The other end of the strap is folded and stitched in place. Must be attached using standard 3" framing nails. Provides an anchor point with a tested failure strength, provided the folded stitched end is attached at the top plate of the wall or truss with two ardox nails.



High Rise - Designed to fit up to 50 mm diameter rebar. Easily installed in shear walls or columns. Can also be installed by inserting an 8" piece of rebar through the strap's looped end, then inserting that end 4" into poured concrete. When the fall hazard has been eliminated from the perimeter, e.g. the exterior wall has been erected, the Safe-T-Strap is removed by cutting it off at the base.

ITEM#	Description
FP-LOWRISE	Low rise Safe-T-Strap™
FP-HIGHRISE	High rise Safe-T-Strap™

Squids® 3110 Tool Lanyard

- Tethers tools to worker to help prevent injury and lost productivity from dropped tools.
- Stretchable cord surrounded by tubular nylon webbing with silver mylar reflective thread.
- Lock stitching at both ends for extra security.
- Cord stretches for full range of motion:
 - Standard: 35" to 42" / .89 m to 1.1 m
 - Extended: 42" to 54" / 1.1 m - 1.4 m
- Aluminum carabiner on each end for tool attachment.
- Maximum safe working capacity: 10 lbs (4.53 kg).



ITEM#	Description
FP-3110	Tool lanyard, black



Res-Q Man® Positioning System

- Can be activated by one person for positioning work.
- Great for work where soft bases are a problem, e.g. grain elevators, over water, or in aggregate silos.
- Can be used with a harness, seat, or stretcher.
- Excellent for work where movement up and down a structure is required, e.g. ship building, window washing, aerial lifts, and cable car rescue.
- Works well for confined space applications and bridge inspection.



NORTH
by Honeywell

ITEM#	Description
FP-FP5/6400K/200	Res-Q Man® positioning system with carabiner, ascender handle, and 200' of kernmantle rope



Rope Terminator Plate

Used to terminate a 5/8" (16 mm) diameter, 3 strand, double braid, or kernmantle rope lifeline. The plate provides a quick, reusable field termination that eliminates the need for knots and factory terminations.

Note: Requires connecting hardware.

MSA

ITEM#	Description
FP-SRIW1000	5/8" Termination plate

Anchorage Slings

FP-SFP22N002B



FP-SFP2267406

MSA

ITEM#	Description
FP-SFP22N002B	Anchorage choker sling, size small
FP-SFP2267406	Suretyman anchorage sling

Anchorage Cable Sling

- Standard lengths of 2', 4', and 6', custom lengths also available.
- Vinyl coated.
- 1/4" Galvanized cable.



MSA

ITEM#	Description
FP-SFP3267502	Anchorage cable sling, 2' length
FP-SFP3267504	Anchorage cable sling, 4' length
FP-SFP3267506	Anchorage cable sling, 8' length

Bolt D-Ring with Hole

- Permanent anchorage connector.
- Attaches to bottom of I-beam flange, user supplies bolt.
- Designed for horizontal installation.



MSA

ITEM#	Description
FP-10003213	Bolt D-ring with hole

Permanent Roof Anchors

Available in five sizes and fits all pitches of roof trusses or rafters. Installs easily without the use of special tools and includes UV resistant neoprene flashing to help prevent roof leakage. The low profile, brown color of the exposed portion of the roof anchor makes it unobtrusive on a finished roof.



- All steel construction to last the life of the roof with minimal maintenance.
- Can be used for Dyna-Line® and Sure-Line® temporary horizontal lifelines.
- Available sizes: 2" x 4", 2" x 6", 2" x 8", 2" x 10", 2" x 12".
- Meets applicable OSHA and ANSI standards.

MSA

ITEM#	Permanent Roof Anchors
FP-10016468	For use with 2" x 4" trusses/ beams
FP-10017593	For use with 2" x 6" trusses/ beams
FP-10017594	For use with 2" x 8" trusses/ beams
FP-10017595	For use with 2" x 10" trusses/ beams
FP-10017596	For use with 2" x 12" trusses/ beams



Wire Clasp

Easy and simple installation.

MSA

ITEM#	Description
FP-10003208	Medium wire clasp, diameter 4-1/8"

More

Fall protection

products available

Call for details